

ALARM-A201P-16WE Wireless Control Panel



- Simple and elegant appearance design
- Wi-Fi network for cloud communication
- Friendly app interface makes installation and use easier
- Up to 2000 m radio signal transmission range in open space

▪ Specification

Model		ALARM-A201P-16WE
Capacity	Installer	3
	User	12
	Areas	4
	Wireless zones	16
	Wireless keypads	4
	Wireless sounders	4
	Wireless keyfobs	16
	Admin	1
	Logs	1000
Communication	Transmission technology	868.0-868.6 MHz
	Transmission range (free space)	up to 2000 m
	Maximum effective radiated power (ERP)	25 mW max
	Radio signal modulation	2GFSK
	Encryption	AES-128
	Ethernet	1 8P8C socket
	Ethernet speed	≤10Mbps
	Wi-Fi	802.11 b/g/n
Software features	Upgrade OTA	Yes
Notifications	APP notifications	Yes
	Event types	Alarms Faults System Events Operations
Indication	Indication method	LED
Hardware features	Tamper-Proof	Yes
Power Supply	Mains power	110-240 V~, 50/60 Hz

	Power consumption	max current: 0.2 A quiescent current: 90 mA
Electrical characteristics	Built-in backup battery	Yes
	Battery life	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
General	Dimension (W×H×D)	165 x 165 x 37.5 mm
	Weight	400 g
	Operation temperature	-10 °C to +55 °C
	Operation humidity	10% to 90%
	Shell material	Plastic

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HiLook